

Military Communications

RCTS-004 Radio Test Set



The RCTS-004 provides "State of the Art" capabilities for semi-automated testing of Canadian IRIS communications systems

RCTS-004 Radio Test Systems

The RCTS-004 RadioTest System is made up of the general purpose TS-4317 Communication Test Set in association with the J-4843A Generic Applique Housing with RPM-004 (PL-5005) and PS-001 (PP-8468) LRU Power Supply. The RCTS-004 RadioTest System is a self-contained, transportable, semi-automated Test System that may be used for a "go/no-go" evaluation, full functional testing and troubleshooting. The RCTS-004 RadioTest System is currently being used by the Canadian Military to verify, test and repair the Canadian IRIS Family of Radios. All LRUs listed below can be verified, tested and repaired when used in conjunction with the Maintenance Group (Cables, Repair Manuals, Special Tools, etc.) supplied by Aeroflex.

CNR(P) Radio

CNR(P) VIU

LAR

RPM-004 CANADA IRIS RPM ACCESSORIES

TF-400	BIT Test Adapter for PL-5005
LK-400	Lockout Key for PL-5005

PS-001 (PP-8468) Generic LRU Power Supply

The PS-001 (PP-8468) connects to the bottom of the RCTS configuration to supply primary power for Units Under Test (UUT) and, in some cases, to the J-4843A and RPM-004 (PL-5005). The PS-001 (PP-8468) is capable of supplying programmable voltage levels from 3 to 30 V at up to 20 A. Additional voltages are provided for secondary needs.

PS-001 (PP-8468) Generic LRU Power Supply Configurations

Supply Output	Output Voltage (VDC)	Line Regulation %	Total Regulation %	Peak Ripple (mV)	Minimum Load(A)	Typical Load(A)	Maximum Load(A)
Switched Outputs:							
1	3.00 - 14.99	±2.0 (NL-FL)	±7 (NL-FL)	<220	0.8	N/A	10
1	15.00 - 30.00	±2.0 (NL-FL)	±7 (NL-FL)	<220	0.8	N/A	20
2	2.50 - 5.00	±8.0 (NL-FL)	±12 (NL-FL)	<70	0.8	N/A	2
3	2.00 - 28.00	±8.0 (NL-FL)	±12 (NL-FL)	<70	0.8	N/A	1
4	6	±2.0 (NL-FL)	±4 (NL-FL)	<70	0.5	0.5	1
5	12	±2.0 (NL-FL)	±10 (NL-FL)	<70	0.2	0.35	1
Continuous Outputs:							
6	24	±2.0 (10% FL-FL)	±8(10% FL-FL)	<70	0.1	1.5	1.8
7	5	±2.0 (10% FL-FL)	±4(10% FL-FL)	<70	2.2	3	4
8	15	±2.0 (10% FL-FL)	±4(10% FL-FL)	<70	0.75	1	2
9	15	±2.0 (10% FL-FL)	±4(10% FL-FL)	<70	0.075	0.1	0.5

EXPORT CONTROL:

This product is controlled for export under the International Traffic in Arms Regulations (ITAR). A license from the U.S. Department of State is required prior to the export of this product from the United States.

EXPORT WARNING:

Aeroflex's military products are controlled for export under the International Traffic in Arms Regulations (ITAR) and may not be sold or proposed or offered for sale to certain countries including: Belarus, Burma, China, Cuba, Haiti, Iran, Liberia, Libya, North Korea, Somalia, Syria, Sudan, and Vietnam. See ITAR 126.1 for complete information.

FINLAND

Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] 8131 2926-0
Fax: [+49] 8131 2926-130

INDIA

Tel: [+91] 80 5115 4501
Fax: [+91] 80 5115 4502

KOREA

Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UK Burnham

Tel: [+44] (0) 1628 604455
Fax: [+44] (0) 1628 662017

UK Cambridge

Tel: [+44] (0) 1763 262277
Fax: [+44] (0) 1763 285353

UK Stevenage

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA

Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352



As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2006.

www.aeroflex.com
info-test@aeroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.