

Avionics

DT200 ARINC 429/CSDB DATABUS ANALYZER



AEROFLEX
A passion for performance.

Powerful capabilities for avionics maintenance

FEATURES

- CSDB capability for Collins ProLine Avionics
- Light weight, battery operated
- Manages multiple data words
- Clearly displays subfields
- Manipulates data with such features as FREEZE, SCROLL and CLEAR

Consider these additional features:

- Receives and displays data in hexadecimal, binary, or engineering units
- Transmits multiple words at selected rates
- Identifies failures with breakpoint trigger pulse and history features
- Converts digital data to DC
- General purpose recording mode for lab or flight test
- Presents data transients as graphic time plots
- Operates anywhere for up to 6 hours on rechargeable battery
- Easy setup with menu selections

The DATATRAC 200's advanced features will handle all your troubleshooting needs with a unit that conveniently supports two avionics databus standards, ARINC 429 and CSDB (Commercial Standard Digital Bus). Basic receive and transmit capabilities are extensive.

The DT200 has the ability to manage many data words, clearly display subfields, and manipulate data with such features as freeze, scroll and clear. Other features of the DT200 include dual operation in either ARINC 429 or CSDB modes, data display in hexadecimal, binary or engineering units, general purpose recording mode for lab or flight tests, operate up to 4-6 hours on a rechargeable battery.

The DT200's light weight provides for easy usage in either a bench or ramp environment.

GENERAL SPECIFICATIONS

ARINC 429 RECEIVE

Bus Frequency

12.5 or 100 KHz (selectable)

Input Levels

+ 6.5 VDC to 13.5 VDC (A to B)

Impedance

12.0 K Ohms

Display Format

Hexadecimal, binary, or engineering units

Maximum Labels

255 per SDI value

Breakpoint Conditions

EQ, NEQ, OR, GT, LT, /GT/, /LT/.

Break History

85 words per label, 16 labels

Record Intervals

10 ms to 5 s (selectable)

Record Capacity

1-3 labels (34 min. for single label at 1/second)

Record Playback

Graphics plots, hex list, or DC output

ARINC 429 TRANSMIT

Bus Frequency

12.5 or 100 KHz (selectable)

Output Levels

+ 10.0 VDC (A to B)

Output Impedance

75 Ohms

Display Format

Hexadecimal

Maximum Labels

16

D/A Range

+ 5.0 VDC, 8-bits

D/A Scaling

100%, 50%, or 12.5% of digital word applied to full output range (full scale offset selection)

Trigger Pulse

+ 5 VDC, 0.5 ms

Burst Mode

1-99 burst output at selectable rate

CSDB RECEIVE

Bus Frequency

12.5 or 50 KHz (select-able)

Input Levels

+ 2.0 TO 6.0 VDC (A to B)

Impedance

8.0 K Ohms

Word Update

3 ms to 5 sec

Display Format

Hexadecimal, binary, or engineering units

Maximum Labels

16

Breakpoint Conditions

EQ, NEQ, OR, GT, LT, /GT/, /LT/

Break History

51 words

Record Intervals

10 ms to 5 sec. (selectable)

Record Capacity

2-3 words (20 minutes for 2 words at 1 per second)

Record Playback

Graphics plots, hex list, or DC output

CSDB TRANSMIT

Bus Frequency

12.5 or 50 KHz (selectable)

Output Levels

+ 3.0 - 5.0 VDC (A to B)

Output Impedance

100 Ohms

Display Format

Hexadecimal

Maximum Labels

16

D/A Range

+ 5.0 VDC, 8-bits

D/A Scaling

100%, 50%, or 12.5% of digital word applied to output range (full scale offset selection)

Trigger Pulse

+ 5 VDC, 0.5 ms

Burst Mode

1-99 burst output at selectable rate

PHYSICAL CHARACTERISTICS

Weight

7.5 lbs (3.4 kg)

Width

12.5" (31.75 cm)

Height

5.0" (12.7 cm)

Depth

11.6" (29.46 cm)

Power Requirements

7.0 Watts at 110 VAC/60 Hz 8.4 Watts at 28 VDC or internal battery

Display

1.7" x 6.0" LCD with 8 lines x 40 char. mode or 64 x 256 dot graphics mode. Front panel dimming control.

VERSIONS, OPTIONS AND ACCESSORIES

When ordering, please include the Order Number listed below:

Ordering Numbers	Description
985	DT200-00 ARINC 429/CSDB Databus Analyzer (specify 110 V or 220 V requirement)

STANDARD ACCESSORIES

Battery charger, Operations Manual

EXTENDED WARRANTY

84381	Extended standard warranty 36 months with scheduled calibration
84382	Extended standard warranty 60 months with-scheduled calibration

CHINA Beijing

Tel: [+86] (10) 6467 2761 2716
Fax: [+86] (10) 6467 2821

CHINA Shanghai

Tel: [+86] (21) 6282 8001
Fax: [+86] (21) 62828 8002

FINLAND

Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] 8131 2926-0
Fax: [+49] 8131 2926-130

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

INDIA

Tel: [+91] 80 5115 4501
Fax: [+91] 80 5115 4502

KOREA

Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UK Burnham

Tel: [+44] (0) 1628 604455
Fax: [+44] (0) 1628 662017

UK Stevenage

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA Wichita

Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352

USA New Century

Tel: [+1] (913) 764 2452
Fax: [+1] (913) 782 5104

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2005.

www.aeroflex.com
info-test@aeroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.