

Errata Sheet

ALT-8000 Operation Manual (p/o 88035)

EXPORT CONTROL WARNING: This document contains controlled technology or technical data under the jurisdiction of the Export Administration Regulations (EAR), 15 CFR 730-774. It cannot be transferred to any foreign third party without the specific prior approval of the U.S. Department of Commerce, Bureau of Industry and Security (BIS). Violations of these regulations are punishable by fine, imprisonment, or both.

NOTICE

The following items are applicable to S/W release:
0.0.6 July 1, 2011

ERRATA STATEMENTS (Items to be addressed in the next release):

1. Altitude Indicator Zero feature: Not functional.
2. CDF FMCW Mode: Not functional.
3. Auto Detect feature: Certain combinations of valid FM CW signals fail to be detected correctly and testing does not start. Manual selection of Radio Altimeter type (FMCW/CDF) is suggested.
4. There could be an offset error in altitude for the LRA-700 high altitude which is outside the specification limits.
5. Ethernet Remote Control Interface status reporting not implemented into 488.2/SCPI.
6. When performing testing using a dynamic altitude mode (altitude rate set at a value other than 0) the ALT-8000 does not stop at the programmed maximum or minimum set point.

ERRATA STATEMENTS (Items to be addressed in the Phase II release):

1. Pulse Mode: Not functional.